




































JBoss 7.3.x

 This page has been automatically generated by Cargo's build. Do not edit it directly as it'll be overwritten next time it's generated again.




 With the opening of the JBoss EAP to the public, JBoss decided to have a funny naming convention:

- What Cargo calls [JBoss 6.1.x](#) is what JBoss refers to as JBoss Application Server version 6.1; i.e. the version released in August 2011
- What Cargo calls [JBoss 7.2.x](#) is what JBoss refers to as JBoss Enterprise Application Platform (EAP) version 6.1; i.e. the build from JBoss Application Server (AS) version 7.2 released in May 2013
- What Cargo calls [JBoss 7.3.x](#) is what JBoss refers to as JBoss Enterprise Application Platform (EAP) version 6.2; i.e. the build from JBoss Application Server (AS) version 7.3 released in October 2013
- What Cargo calls [JBoss 7.4.x](#) is what JBoss refers to as JBoss Enterprise Application Platform (EAP) version 6.3; i.e. the build from JBoss Application Server (AS) version 7.4 released in June 2014

Container Features

| Feature name | Java | Ant | Maven2 |
|---------------------------|---|--|--|
| Container Instantiation |  <code>ContainerFactory.createContainer("jboss73x" ...)</code> |  <code><cargo containerId="jboss73x" .../></code> |  <code><containerId>jboss73x</containerId></code> |
| Local Container |  |  |  |
| Container Classpath |  |  |  |
| Container Start |  |  |  |
| Container Stop |  |  |  |
| Container Timeout |  |  |  |
| Embedded Container |  |  |  |
| Installed Container |  <code>o.c.c.c.jboss.JBoss73xInstalledLocalContainer</code> |  |  |
| Passing system properties |  |  |  |
| Installer |  |  |  |
| Remote Container |  <code>o.c.c.c.jboss.JBoss73xRemoteContainer</code> |  |  |

Configuration Features

| Feature name | Java | Ant | Maven2 | Comment |
|--|---|---|---|---------|
| Standalone Local Configuration for installed container |  <code>o.c.c.c.jboss.JBoss73xStandaloneLocalConfiguration</code> |  |  | |

| | | | | | |
|---|--|---|--|--|--|
| Standalone Local Configuration for embedded container | | | | | |
| Existing Local Configuration for installed container | | <code>o.c.c.c.jboss.JBoss71xExistingLocalConfiguration</code> | | | |
| Existing Local Configuration for embedded container | | | | | |
| Runtime Configuration | | <code>o.c.c.c.jboss.JBoss7xRuntimeConfiguration</code> | | | |
| Static deployment of WAR | | | | | |
| Static deployment of expanded WAR | | | | | |
| Static deployment of EJB | | | | | |
| Static deployment of EAR | | | | | |
| Static deployment of RAR | | | | | |
| Static deployment of (JBoss) HAR | | | | | |
| Static deployment of (JBoss) SAR | | | | | |
| Static deployment of (JBoss) AOP | | | | | |
| Static deployment of files | | | | | |
| Static deployment of OSGi Bundles | | | | | |

Deployer Features

| Feature name | Java | Ant | Maven2 | Comment |
|--------------------|--|-----|--------|---------|
| Installed Deployer | <code>o.c.c.c.jboss.JBoss7xInstalledLocalDeployer</code> | | | |
| Embedded Deployer | | | | |
| Remote Deployer | <code>o.c.c.c.jboss.JBoss7xRemoteDeployer</code> | | | |

Other Features

| Feature name | Java | Ant | Maven2 | Comment |
|--------------|------|-----|--------|---------|
| Debugging | | | | |

Supported Configuration properties

The tables below list both the [general configuration properties](#) as well as the container-specific ones.

Standalone Local Configuration Properties

For installed container `o.c.c.c.jboss.JBoss73xInstalledLocalContainer`

| Property name | Java Property | Supported? | Default value |
|------------------------------|---|------------|--|
| <code>cargo.hostname</code> | <code>GeneralPropertySet.HOSTNAME</code> | | <code>localhost</code> |
| <code>cargo.java.home</code> | <code>GeneralPropertySet.JAVA_HOME</code> | | <code>JAVA_HOME</code> version 6 or newer |

| | | | |
|--|---|---|------------|
| cargo.jboss.ajp.port | JBossPropertySet.JBOSS_AJP_PORT | ✓ | 8009 |
| cargo.jboss.configuration | JBossPropertySet.CONFIGURATION | ✓ | standalone |
| cargo.jboss.deployment.dir | JBossPropertySet.ALTERNATIVE_DEPLOYMENT_DIR | ✓ | N/A |
| cargo.jboss.management-http.port | JBossPropertySet.JBOSS_MANAGEMENT_HTTP_PORT | ✓ | 9990 |
| cargo.jboss.management-native.port | JBossPropertySet.JBOSS_MANAGEMENT_NATIVE_PORT | ✓ | 9999 |
| cargo.jboss.modules.dir | JBossPropertySet.ALTERNATIVE_MODULES_DIR | ✓ | modules |
| cargo.jboss.remoting.transport.port | JBossPropertySet.JBOSS_REMOTING_TRANSPORT_PORT | ✓ | 4447 |
| cargo.jvmargs | GeneralPropertySet.JVMARGS | ✓ | N/A |
| cargo.logging | GeneralPropertySet.LOGGING | ✓ | medium |
| cargo.port.offset | GeneralPropertySet.PORT_OFFSET | ✓ | 0 |
| cargo.process.spawn | GeneralPropertySet.SPAWN_PROCESS | ✓ | false |
| cargo.protocol | GeneralPropertySet.PROTOCOL | ✗ | http |
| cargo.remote.password | RemotePropertySet.PASSWORD | ✓ | N/A |
| cargo.remote.username | RemotePropertySet.USERNAME | ✓ | N/A |
| cargo.runtime.args | GeneralPropertySet.RUNTIME_ARGS | ✓ | N/A |
| cargo.servlet.port | ServletPropertySet.PORT | ✓ | 8080 |
| cargo.servlet.users | ServletPropertySet.USERS | ✓ | N/A |
| cargo.standalone.ignoreNonExistingProperties | GeneralPropertySet.IGNORE_NON_EXISTING_PROPERTIES | ✓ | N/A |



Datasource and Resource configuration

In addition to the forementioned properties, this container configuration can also set up datasources and/or resources.

For more details, please read: [DataSource and Resource Support](#).


Existing Local Configuration Properties

For installed container `o.c.c.c.jboss.JBoss73xInstalledLocalContainer`

| Property name | Java Property | Supported? | Default value | Javadoc |
|------------------------------------|---|------------|-------------------------------------|---------|
| cargo.hostname | GeneralPropertySet.HOSTNAME | ✓ | localhost | ★ |
| cargo.java.home | GeneralPropertySet.JAVA_HOME | ✓ | <i>JAVA_HOME version 6 or newer</i> | ★ |
| cargo.jboss.configuration | JBossPropertySet.CONFIGURATION | ✓ | standalone | ★ |
| cargo.jboss.management-http.port | JBossPropertySet.JBOSS_MANAGEMENT_HTTP_PORT | ✗ | N/A | |
| cargo.jboss.management-native.port | JBossPropertySet.JBOSS_MANAGEMENT_NATIVE_PORT | ✓ | 9999 | ★ |
| cargo.jboss.modules.dir | JBossPropertySet.ALTERNATIVE_MODULES_DIR | ✓ | modules | ★ |
| cargo.port.offset | GeneralPropertySet.PORT_OFFSET | ✓ | 0 | ★ |
| cargo.process.spawn | GeneralPropertySet.SPAWN_PROCESS | ✓ | false | ★ |

| | | | | |
|-----------------------|-----------------------------|---|------|---|
| cargo.protocol | GeneralPropertySet.PROTOCOL | ✓ | http | ★ |
| cargo.remote.password | RemotePropertySet.PASSWORD | ✓ | N/A | ★ |
| cargo.remote.username | RemotePropertySet.USERNAME | ✓ | N/A | ★ |
| cargo.servlet.port | ServletPropertySet.PORT | ✓ | 8080 | ★ |

Runtime Configuration Properties

 Before using the JBoss remote deployer, please read: [JBoss Remote Deployer](#)

For remote container o.c.c.c.jboss.JBoss73xRemoteContainer

| Property name | Java Property | Supported? | Default value | Javadoc |
|------------------------------------|---|------------|---------------|---------|
| cargo.hostname | GeneralPropertySet.HOSTNAME | ✓ | localhost | ★ |
| cargo.jboss.clustered | JBossPropertySet.CLUSTERED | ✗ | N/A | |
| cargo.jboss.configuration | JBossPropertySet.CONFIGURATION | ✗ | N/A | |
| cargo.jboss.management-http.port | JBossPropertySet.JBOSS_MANAGEMENT_HTTP_PORT | ✗ | N/A | |
| cargo.jboss.management-native.port | JBossPropertySet.JBOSS_MANAGEMENT_NATIVE_PORT | ✓ | 9999 | ★ |
| cargo.jboss.profile | JBossPropertySet.PROFILE | ✗ | N/A | |
| cargo.remote.password | RemotePropertySet.PASSWORD | ✓ | N/A | ★ |
| cargo.remote.uri | RemotePropertySet.URI | ✗ | N/A | |
| cargo.remote.username | RemotePropertySet.USERNAME | ✓ | N/A | ★ |