

confluence-reporting-maven-plugin-4.0.0-SNAPSHOT - deploy

confluence-reporting:deploy

Generate Project's documentation in confluence's wiki format and deploy it

Mojo Attributes

- Requires a Maven 2.0 project to execute.

Required Parameters

Name	Type	Description
checkoutDirectoryName	String	The directory name to checkout right after the scm url Default value is \${project.artifactId}
outputDirectory	File	No description.
spaceKey	String	Confluence target confluence's spaceKey

Optional Parameters

Name	Type	Description
anonymousConnection	String	The scm anonymous connection url. Default value is \${project.scm.connection}
attachmentFolder	File	attachment folder Default value is \${basedir}/src/site/confluence/attachments
childrenFolder	File	children folder Default value is \${basedir}/src/site/confluence/children
developerConnection	String	The scm developer connection url. Default value is \${project.scm.developerConnection}
encoding	String	The file encoding of the source files. Default value is \${project.build.sourceEncoding}
endPoint	String	Confluence end point url Default value is http://localhost:8080/rpc/xmlrpc
labels	List	Labels to add
parentPageTitle	String	Confluence target confluence's spaceKey Default value is Home
password	String	Confluence password
properties	Map	additional properties pass to template processor
removeSnapshots	boolean	During publish of documentation related to a new release, if it's true, the pages related to SNAPSHOT will be removed Default value is false
serverId	String	Issue 39 Server's <code><code>id</code></code> in <code><code>settings.xml</code></code> to look up username and password. Defaults to <code><code>\${url}</code></code> if not given.
siteDescriptor	File	site xml descriptor Default value is \${basedir}/src/site/confluence/site.xml
templateWiki	File	Home page template source. Template name will be used also as template source for children Default value is \${basedir}/src/site/confluence/template.wiki
title	String	Confluence Page Title
username	String	Confluence username
webAccessUrl	String	The scm web access url. Default value is \${project.scm.url}
wikiFilesExt	String	Children files extension Default value is .wiki

Parameter Details

anonymousConnection

The scm anonymous connection url.

Type	java.lang.String
Required	No
Default	\${project.scm.connection}

attachmentFolder

attachment folder

Type	java.io.File
Required	No
Default	\${basedir}/src/site/confluence/attachments

checkoutDirectoryName

The directory name to checkout right after the scm url

Type	java.lang.String
Required	Yes
Default	\${project.artifactId}

childrenFolder

children folder

Type	java.io.File
Required	No
Default	\${basedir}/src/site/confluence/children

developerConnection

The scm developer connection url.

Type	java.lang.String
Required	No
Default	\${project.scm.developerConnection}

encoding

The file encoding of the source files.

Type	java.lang.String
Required	No
Expression	\${encoding}
Default	\${project.build.sourceEncoding}

endPoint

Confluence end point url

Type	java.lang.String
Required	No

Expression	<code>\${confluence.endPoint}</code>
Default	<code>http://localhost:8080/rpc/xmlrpc</code>

labels

Labels to add

Type	<code>java.util.List</code>
Required	No

outputDirectory

No Description.

Type	<code>java.io.File</code>
Required	Yes
Expression	<code>\${project.build.directory/generated-site/confluence}</code>

parentPageTitle

Confluence target confluence's spaceKey

Type	<code>java.lang.String</code>
Required	No
Expression	<code>\${confluence.parentPage}</code>
Default	Home

password

Confluence password

Type	<code>java.lang.String</code>
Required	No
Expression	<code>\${confluence.password}</code>

properties

additional properties pass to template processor

Type	<code>java.util.Map</code>
Required	No

removeSnapshots

During publish of documentation related to a new release, if it's true, the pages related to SNAPSHOT will be removed

Type	<code>boolean</code>
Required	No
Expression	<code>\${confluence.removeSnapshots}</code>
Default	<code>false</code>

serverId

Issue 39

Server's `id` in `settings.xml` to look up username and password.
Defaults to `url` if not given.

Type	java.lang.String
Since	3.1.1
Required	No
Expression	<code>{confluence.serverId}</code>

siteDescriptor

site xml descriptor

Type	java.io.File
Since	3.3.0
Required	No
Default	<code>{basedir}/src/site/confluence/site.xml</code>

spaceKey

Confluence target confluence's spaceKey

Type	java.lang.String
Required	Yes
Expression	<code>{confluence.spaceKey}</code>

templateWiki

Home page template source. Template name will be used also as template source for children

Type	java.io.File
Required	No
Default	<code>{basedir}/src/site/confluence/template.wiki</code>

title

Confluence Page Title

Type	java.lang.String
Since	3.1.3
Required	No
Expression	<code>{project.build.finalName}</code>

username

Confluence username

Type	java.lang.String
Required	No
Expression	<code>{confluence.userName}</code>

webAccessUrl

The scm web access url.

Type	java.lang.String
Required	No
Default	\${project.scm.url}

wikiFilesExt

Children files extension

Type	java.lang.String
Since	3.2.1
Required	No
Expression	\${wikiFilesExt}
Default	.wiki