

FindBugs Plugin

When using the FindBugs plugin you can specify certain rules to run or just give a list of rules not to run:

Go here <http://findbugs.sourceforge.net/api/edu/umd/cs/findbugs/detect/package-summary.html> to see the list of names that are allowed in the comma delimited list These are the names that can be used in the "visitor" sections below.

```
<reporting>
  <plugins>
    <plugin>
      <groupId>org.codehaus.mojo</groupId>
      <artifactId>findbugs-maven-plugin</artifactId>
      <configuration>
        <xmlOutput>true</xmlOutput>
        <xmlOutputDirectory>
          ${project.build.directory}/findbugs-reports
        </xmlOutputDirectory>
        <threshold>Medium</threshold>
        <effort>Max</effort>
        <excludeFilterFile>findbugs-exclude.xml</excludeFilterFile>
        <includeFilterFile>findbugs-include.xml</includeFilterFile>
        <visitors>
          FindDeadLocalStores,UnreadFields
        </visitors>
        <omitVisitors>
          FindDeadLocalStores,UnreadFields
        </omitVisitors>
        <onlyAnalyze>org.codehaus.mojo.findbugs.*</onlyAnalyze>
        <pluginList>/libs/fb-contrib/fb-contrib-2.8.0.jar</pluginList>
        <debug>>false</debug>
        <relaxed>>true</relaxed>
      </configuration>
    </plugin>
  </plugins>
</reporting>
```