

PacksPanel

Usage

Allows the user to select the packs to be installed. This panel also allows grouping of packs. Look at [InstallationGroupPanel](#) description to get more details.

IzPack automatically sets reserved variables depending on the packs selected by the user or an unattended installation (auto-install.xml) to be installed:

```
izpack.selected.<packname>
```

where `<packname>` is the name attribute `<pack name="...">` of the pack selected. If the pack is selected, the condition validates true.

Translations

The contents of PacksPanel can be translated, in order to present a different name and description of the packs for each language.

In order to provide internationalization for the PacksPanel, you have to add a resource `packsLang.xml_xyz` to the installation descriptor (install.xml) where `xyz` is the ISO3 code of the language in lowercase.

Example:

The installation descriptor (install.xml)

```
<resources>
  <res id="packsLang.xml_eng" src="i18n/myPacksLang.xml_eng" />
</resources>
```

The IzPack translation file uses reserved IDs for the single translation items.

For translating the short name of the pack use the pack **name** as the `id` attribute of each translation item. For translating a pack description use the pack name suffixed by `.description` as the translation item key.

The packsLang.xml_eng file referred by the according resource ID

```
<langpack>
  <str id="myApplicationPack" txt="Main Application"/>
  <str id="myApplicationPack.description" txt="A description of my main application
package"/>
  [...]
</langpack>
```